

IBS special cleaner WAS 20.100

SKU: 20.100

Alkaline, aqueous high-performance cleaning concentrate. Intensive cleaner for removing heavy soiling (e.g. coking, soot, graphite, pigments). For use in all conventional ultrasonic and flood cleaning systems. Best cleaning results even when wiping.



Applications:

Optimally matched to all conventional ultrasonic devices and flood cleaning systems. Can also be used in wiping processes.

Areas of application:

- For powerful cleaning of parts and components from production, manufacturing, process technology, engine repair and repair workshops of all kinds

- Oil / filters, pistons, cylinder heads, diesel particulate filters (DPF), diesel injection pumps, injection nozzles, carburettors, radiators
- turbochargers, wheel bearings
- Tool and mould cleaning (blind bores), injection moulds
- Cutlery, precision stainless steel tubes and wire products, screws, bulk goods
- Electrical components, precision tools, machine components

Contamination:

- strong with stubborn stains
- Burnt-on: heavy coking / carbon deposits oil carbon, soot, graphite, pigments
- Incrustations, resins and waxes, lapping, polishing and abrasive residues
- Bitumen ("earth pitch")
- Metal abrasion / swarf
- Greases, oils, coolants and lubricants, anti-corrosion oils

Dosage:

The product is a concentrate that must be diluted with sufficient water.

Our recommendation for the dosage:

- Light to normal soiling 2-3 %
- heavy soiling 4-5 %

Advantages:

- Powerful with carbon and pigments
- Powerful yet gentle cleaning with corrosion protection (steel, stainless steel, non-ferrous metals – aluminium)
- effective with high cleaning power from 25 °C, economical, energy and cost-saving

- demulsifying and separator-friendly – suitable for aluminium separators
- the treated parts can be easily galvanised or painted after cleaning
- silicone-free

Applications/areas of use

Technical data

Container size:	1000 L, 20 L, 200 L
PH value:	> 11,5
Colour:	violet
Odour:	Characteristic
Foaming behaviour:	foaming
Application concentration:	3 - 5 %
Operating temperature:	25 - 60° C
Density:	1.05-1.07 g/cm ³
Labelling:	GHS07